

09-18-00

1c490 U.S. PTO

Please type a plus sign (+) inside this box → ☐

PTO/SB/05 (4/98)
 Approved for use through 09/30/2000. OMB 0651-0032
 Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
 Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. YOR9-2000-0144US1 (8728-375)

First Inventor or Application Identifier CHEN

Title SYSTEM AND METHOD FOR MANAGING A

Express Mail Label No. EL599449326US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages 38]
(preferred arrangement set forth below)
 - Descriptive title of the invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the invention
 - Brief Summary of the invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 4]
4. Oath or Declaration [Total Pages 2]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 16 completed)
 - c. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

* NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.37), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.33).

ADDRESS TO:

Assistant Commissioner for Patents
 Box Patent Application
 Washington, DC 20231

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☒ Assignment Papers (cover sheet & document(s))
8. ☐ 37 C.F.R. § 3.73(b) Statement (when there is an assignee) ☒ Power of Attorney
9. ☐ English Translation Document (if applicable)
10. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. ☐ * Small Entity Statement(s) filed in prior application, Status still proper and desired (PTO/SB/09-12)
14. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
15. ☐ Other: _____

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: _____

Prior application information: Examiner _____ Group / Art Unit: _____

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label

(Insert Customer No. or Attach bar code label here)

or ☐ Correspondence address below

Name	Frank V. DeRosa				
Address	F. Chau & Associates, LLP 1900 Hempstead Turnpike, Suite 501				
City	East Meadow	State	New York	Zip Code	11554
Country	USA	Telephone	516-357-0091	Fax	516-357-0092

Name (Print/Type)	Frank V. DeRosa	Registration No. (Attorney/Agent)	43,584
Signature	<i>Frank V. DeRosa</i>	Date	9/15/00

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Patent Application, Washington, DC 20231

09/15/00
 09/663812
 JCS64 U.S. PTO

FEE TRANSMITTAL

for FY 2000

Patent fees are subject to annual revision.
Small Entity payments must be supported by a small entity statement,
otherwise large entity fees must be paid. See Forms PTO/SB/09-12.
See 37 C.F.R. §§ 1.27 and 1.28.

TOTAL AMOUNT OF PAYMENT (\$ 748.00

Complete if Known

Application Number	
Filing Date	September 15, 2000
First Named Inventor	Julian C. Chen
Examiner Name	
Group / Art Unit	
Attorney Docket No.	YOR9-2000-0144US1 (8728-375)

METHOD OF PAYMENT (check one)

1. ☒ The Commissioner is hereby authorized to charge indicated fees and credit any overpayments to:

Deposit Account Number 50-0510/IBM

Deposit Account Name IBM/Yorktown Heights

- ☒ Charge Any Additional Fee Required
Under 37 CFR §§ 1.16 and 1.17

2. ☐ Payment Enclosed:

☐ Check ☐ Money Order ☐ Other

FEE CALCULATION

1. BASIC FILING FEE

Large Entity	Small Entity	Fee Code	Fee (\$)	Fee Code	Fee (\$)	Fee Description	Fee Paid
101	690	201	345			Utility filing fee	690
106	310	206	155			Design filing fee	
107	480	207	240			Plant filing fee	
108	690	208	345			Reissue filing fee	
114	150	214	75			Provisional filing fee	

SUBTOTAL (1) (\$ 690.00

2. EXTRA CLAIM FEES

Total Claims	Extra Claims	Fee from below	Fee Paid
21	20** = 1	18	18
3	3** = 0	78	0
Multiple Dependent		260	

**or number previously paid, if greater; For Reissues, see below

Large Entity	Small Entity	Fee Code	Fee (\$)	Fee Code	Fee (\$)	Fee Description	Fee Paid
103	18	203	9			Claims in excess of 20	
102	78	202	39			Independent claims in excess of 3	
104	260	204	130			Multiple dependent claim, if not paid	
109	78	209	39			** Reissue independent claims over original patent	
110	18	210	9			** Reissue claims in excess of 20 and over original patent	

SUBTOTAL (2) (\$ 18.00

FEE CALCULATION (continued)

3. ADDITIONAL FEES

Large Entity	Small Entity	Fee Code	Fee (\$)	Fee Code	Fee (\$)	Fee Description	Fee Paid
105	130	205	65			Surcharge - late filing fee or oath	
127	50	227	25			Surcharge - late provisional filing fee or cover sheet	
139	130	139	130			Non-English specification	
147	2,520	147	2,520			For filing a request for reexamination	
112	920*	112	920*			Requesting publication of SIR prior to Examiner action	
113	1,840*	113	1,840*			Requesting publication of SIR after Examiner action	
115	110	215	55			Extension for reply within first month	
116	380	216	190			Extension for reply within second month	
117	870	217	435			Extension for reply within third month	
118	1,360	218	680			Extension for reply within fourth month	
128	1,850	228	925			Extension for reply within fifth month	
119	300	219	150			Notice of Appeal	
120	300	220	150			Filing a brief in support of an appeal	
121	260	221	130			Request for oral hearing	
138	1,510	138	1,510			Petition to institute a public use proceeding	
140	110	240	55			Petition to revive - unavoidable	
141	1,210	241	605			Petition to revive - unintentional	
142	1,210	242	605			Utility issue fee (or reissue)	
143	430	243	215			Design issue fee	
144	580	244	290			Plant issue fee	
122	130	122	130			Petitions to the Commissioner	
123	50	123	50			Petitions related to provisional applications	
126	240	126	240			Submission of Information Disclosure Stmt	
581	40	581	40			Recording each patent assignment per property (times number of properties)	40.00
146	690	246	345			Filing a submission after final rejection (37 CFR § 1.129(a))	
149	690	249	345			For each additional invention to be examined (37 CFR § 1.129(b))	


Other fee (specify) _____

Other fee (specify) _____

*Reduced by Basic Filing Fee Paid

SUBTOTAL (3) (\$ 40.00

SUBMITTED BY

Name (Print/Type)	Frank V. DeRosa	Registration No. (Attorney/Agent)	43,584	Telephone	(516) 357-0091
Signature		Date	9/15/00		

WARNING:

Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Assistant Commissioner for Patents
Washington, D.C. 20231
Sir:

ATTORNEY DOCKET: YOR9-2000-0144US1 (8728-375)
Date: September 15, 2000
Express Mail Label: EL599449326US
Date of Deposit: September 15, 2000

Transmitted herewith for filing is the Patent Application of:

Inventors: Julian C. Chen, Dimitri Kanevsky, Wlodek W. Zadrozny

For: SYSTEM AND METHOD FOR MANAGING A TEXTUAL ARCHIVE USING SEMANTIC UNITS

Enclosed are: [X] 32 sheets of specification; [X] 1 sheet(s) of Abstract; [X] 5 sheet(s) of claims; [X] 4 sheet(s) of drawing(s);

[X] An assignment of the invention to International Business Machines Corporation with Recordation Form.

[X] Declaration and Power of Attorney.

[] A certified copy of a _____ application, from which priority under Title 35 USC §119 is claimed.

[] Associate Power of Attorney.

The filing fee has been calculated as shown below:

(Col. 1)		(Col. 2)	OTHER THAN A SMALL ENTITY	
FOR:	NO. FILED	NO. EXTRA	RATE	FEE
BASIC FEE				\$690.00
TOTAL CLAIMS	21 -20 =	1	X \$18 =	18.00
INDEP CLAIMS	3-3 =	0	X \$78 =	0
MULTIPLE DEPENDENT CLAIMS PRESENTED			+ 260 =	
			TOTAL	\$ 708.00

If the difference in Col. 1 is less than zero, enter "0" in Col. 2.

[] A check in the amount of \$_____ to cover the [] filing fee(s), [] recording fee is enclosed.

[X] Please charge my Deposit Account No. 50-0510/IBM (Yorktown Heights) in the amount of \$708.00.


[X] The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 50-0510/IBM (Yorktown Heights). A duplicate copy of this sheet is enclosed.

[X] Any additional filing fees required under 37 CFR 1.16.

[X] Any patent application processing fees under 35 CFR 1.17.

Respectfully submitted,

By:


Frank V. DeRosa
Registration No. 43,584


Please address all
correspondence to:

F. CHAU & ASSOCIATES, LLP
1900 Hempstead Tpke., Suite 501
East Meadow, NY 11554
Tel: (516) 357-0091
Fax: (516) 357-0092

Attorney for:
IBM Corporation
Intellectual Property Law Dept.
P.O. Box 218
Yorktown Heights, NY 10598

CERTIFICATION UNDER 37 C.F.R. §1.10

I hereby certify that this Application transmittal and documents referred to as enclosed are being deposited with the United States Postal Service on this date September 15, 2000 in an envelope as "Express Mail Post Office to Addressee" Mailing Label Number EL599449326US addressed to: Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231.


Frank V. DeRosa

**SYSTEM AND METHOD FOR MANAGING
A TEXTUAL ARCHIVE USING SEMANTIC UNITS**

BACKGROUND

1. Technical Field:

5 The present application relates generally to a system and method for managing textual archives and, more particularly, to a system and method for indexing and searching textual archives using semantic units of words, such as syllables and morphemes.

2. Description of Related Art:

10 There are vast library archives that store manuscripts, manuals, written and typed texts in various languages. Moreover, there are various techniques known to those skilled in the art are employed for indexing textual data stored in such archives, as well as searching for target text. For example, techniques similar to those that are used for automatic indexing of audio data can be applied to automatic indexing of handwriting data in general, wherein a word is used as the basic unit for indexing and searching.

15 Typically, with these conventional audio methods, audio data is transcribed (via automatic speech recognition or manually), time stamped and indexed via words. Similar indexing methods are employed for textual manuscripts, wherein the textual manuscripts are processed by AHR

20

(automatic handwriting recognition) or OCR (optical character recognition) systems to produce electronic text in some format (e.g. ASCII). This decoding process generates an index from electronic textual files into stored textual data that can be used for a search and data retrieval in textual archives.

In general, there are various problems associated with word-based indexing and searching systems. In word-based systems, before searching can be started, a vocabulary and a language model based on known words must be generated. Typically, there are always unknown words (that are not accounted for in the language model and vocabulary), which renders the searching mechanism inefficient as it can only work with known words with a good language model score. Furthermore, a searching mechanism that is based on indexing of letters would be very inaccurate since there is a high level of confusability of what letter the individual written symbols represent in unknown words - indeed, people often write inaccurately and some written symbols resemble different characters.

The disadvantages associated with word-based systems are even more apparent with languages in which the unit "word" in a text is ambiguous (such as Chinese language) or in languages that have very large number of word forms (such

as Slavic languages). Indeed, for certain languages such as Chinese and Slavic, traditional word-based methods for indexing data are not readily applicable due to certain features in these languages. For example, for most Asian languages such as Chinese, Japanese, Korean, Thai and Vietnamese, the word boundaries of the character strings do not have "marks" that clearly indicate/define the ends of words such as a blank text (such as the English language and most European languages where the word boundaries are in the printed text or computer text file as "white spaces"). In addition, Slavic languages operate with vocabularies consisting of several million words, which makes it difficult to build a hash table for word-indexing purposes in connection with such enormous vocabularies.

Another disadvantage associated with word-based indexing and searching systems is that certain languages have different fonts and styles for writing characters. These fonts and styles are time dependent. For example, the Chinese characters (ideographs or pictographs, never hieroglyphs) have been developed for about 7000 years. The handwriting styles were fixed at about the 13th century. There are several versions, but for handwriting recognition, there is almost one single style, which is the standard script style (KaiShu). A similar style is the informal

script (XingShu), which is more difficult to recognize. The fonts were fixed in the 10th century, after the invention of printing. Such fonts are still used today, and called "Song Style", after the dynasty of Song (900-1200 A.D.).

5 Similarly, the Russian spelling of words was radically changed after Russian revolution in 1917. For example, one Russian character that occurs often at the end of words was eliminated from the vocabulary.

10 Another difficulty of indexing Chinese textual data, for example, is due to the fact that there are several methods that are being developed for inputting Chinese characters through a keyboard. A first method uses Pinyin, a system for writing characters phonetically with the Roman alphabet. A second method recognizes Chinese characters, so long as the strokes of each character are written in certain order. Currently, the Chinese IBM WorkPad™ supports simplified Chinese, which has fewer characters than traditional Chinese - 7000 versus 10,000 - and fewer strokes in some characters. Finally, a hybrid method allows the first character to be entered phonetically and the following one by strokes.

20 For all of the reasons described above, it is difficult to apply automatic handwriting or OCR recognition of textual data for indexing purposes that use word-based recognition

of handwriting (or typed) input utterance. Accordingly, a need exists in the art for a system and method for indexing and searching textual archive which is independent of fonts and styles and which is operable with unknown words. Such a system would be particularly useful with Asian and Slavic languages, wherein word-based indexing and searching techniques are inefficient for managing textual archives.

SUMMARY OF THE INVENTION

The present invention is directed to a system and method for indexing and searching textual archives using semantic units such as syllables and morphemes. In one aspect of the present invention, a system for indexing a textual archive is provided wherein an AHR (automatic handwriting recognition) system and/or OCR (optical character recognition) system recognizes (decodes) textual input data (handwritten or typed text) into a string of semantic units (e.g., syllables or morphemes) using a statistical language model and vocabulary based on semantic units (such as syllables or morphemes). The string of semantic units that result from a decoding process are stored in a semantic unit database and indexed with pointers to the corresponding textual data in the textual archive.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

In another aspect of the present invention, a system for searching a textual archive is provided, wherein a word (or words) to be searched is rendered into a string of semantic units (e.g., syllables or morphemes) depending on the application. A search engine then compares the string of semantic units (resulting from the input query) against the decoded semantic unit database, and then identifies textual data stored in the textual archive using the indexes that was generated during a semantic unit-based indexing process.

These and other aspects, features and advantages of the present invention will be described and become apparent from the following detailed description of preferred embodiments, which is to be read in connection with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a diagram of a system/method for indexing a textual archive based on semantic units according to an embodiment of the present invention;

Fig. 2 is a diagram of a system/method for constructing a language model based on semantic units according to an embodiment of the present invention;

Fig. 3 is a diagram of a system/method for searching a textual archive that is indexed based on semantic units according to an embodiment of the present invention; and

Fig. 4 is a diagram of a system/method for processing a query according to one aspect of the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

It is to be understood that the present invention may be implemented in various forms of hardware, software, firmware, special purpose processors, or a combination thereof. Preferably, the present invention is implemented in software as an application comprising program instructions that are tangibly embodied on one or more program storage devices (e.g., magnetic floppy disk, RAM, CD ROM, ROM and Flash memory) and executable by any device, machine or platform comprising suitable architecture. It is to be further understood that because some of the constituent system components and method steps depicted in the accompanying Figures are preferably implemented in software, the actual connections between the system components (or the process steps) may differ depending upon the manner in which the present invention is programmed. Given the teachings herein, one of ordinary skill in the

related art will be able to contemplate these and similar implementations or configurations of the present invention.

General Overview

5 The present invention is directed to a system and method for indexing and searching textual archives using semantic units such as syllables and morphemes. In general, with respect to indexing a textual archive, the present invention employs an AHR system and/or OCR system that recognizes (decodes) textual input data (e.g., recorded
10 handwriting data or scanned text data which is stored in the textual archive) into a string of semantic units (e.g., syllables or morphemes) using a vocabulary and statistical language model based on syllables or morphemes, which is preferably constructed upon a large text corpus. The string
15 of semantic units that result from a decoding process are stored in a semantic unit database and indexed to the textual data in the textual archive.

20 During a subsequent search process, a word (or words) to be searched is rendered into a string of semantic units (e.g., syllables or morphemes) depending on the application. A search engine then compares the string of semantic units (resulting from the input query) against the semantic unit database, and then identifies textual data stored in the

archive using an indexing that was generated during the indexing process. Specific details of preferred embodiments of systems and methods for indexing and searching textual data are described below.

5 Advantageously, the use of semantic units allows language models to be constructed which represent semantic information and provides improved decoding accuracy for, e.g., an AHR system based on a vocabulary comprising semantic units. Indeed, as will be evident from the description herein, the use of semantic units for transcribing, indexing and searching textual data is particularly advantageous since such semantic units are clear and the amount of possible semantic units for a given language is finite.

10 Examples of semantic units which may be employed herein for purposes of transcribing, indexing and searching textual data include "syllables" in, e.g., the Chinese language and "morphemes" in, e.g., Slavic languages. For example, the unit morpheme exists in Asian languages such as Chinese, Japanese, Korean, Thai, and Vietnamese. In the Chinese language, each syllable is a morpheme (with very few exceptions where a morpheme consists of more than one syllable). In addition, each syllable is represented by a Chinese character known as a Hanzi. In modern standard

Chinese language (the standard dialect Mandarin, or Putonghua, based on Beijing dialect), the total number of allowed syllables (or Hanzi) is 1400, whereas the number of standard written Chinese characters is 6700 in mainland China and 13,000 in Taiwan.

Furthermore, in the Korean language, there are less than 2400 acoustically allowed syllables. The writing system is based entirely on acoustic syllables (as described herein, the acoustic symbols are used to describe a complexity of the language system for handwriting/textual indexing since, as in a case with Chinese characters, phonetic written representation can be used to represent handwritten and typed words). In the Japanese language, there are only 105 allowed syllables In the Vietnamese language, there are 3000 different syllables and the writing system is based entirely on acoustic syllables. Similarly, languages that have very large number of word forms (e.g., Slavic languages which comprise several million word forms) have relatively small number of morphemes (e.g., the Russian language comprises 50,000 morphemes).

It is to be appreciated that the use of semantic units for indexing and searching textual archives associated with these languages is more efficient and computationally inexpensive than the word-based or word-bag based methods.

YOR9-2000-0144US1 (8728-375)

Consequently, for any language in which conventional word-based techniques for transcribing, indexing and searching textual data is inefficient or inapplicable, the use of semantic units as the basic building block for indexing and searching is particularly advantageous. In addition, because of the finite number of syllables and morphemes, data compression as applied to the present invention is also more efficient. Furthermore, a semantic unit-based approach resolves the problem of unknown words, since all the semantic units are known.

Semantic Unit-Based Indexing

Referring now to Fig. 1, a diagram illustrates a system for indexing a textual archive based on semantic units according to an embodiment of the present invention. It is to be understood that Fig. 1 also represents a high level flow diagram of an indexing method according to one aspect of the present invention. The system 10 comprises a recording device 11 for recording/inputting text data or handwriting data. The recording device 11 may comprise any conventional recording/input device such as a scanner (for scanning typed or written text), electronic notepad (for recording handwritten text) or keyboard (for entering typed text), for example. The recorded text/handwriting data is

stored in textual data storage 12 (or textual archive) and indexed using semantic units as described in detail below.

5 The system 10 further comprises a textual recognition unit 13 which, in a preferred embodiment, is adapted to first recognize the type of textual data (handwriting data, typed text) that is input from either the recording device 11 (real-time) or retrieved from the textual archive 12 (non-real time), and then select the appropriate recognition system. More specifically, the textual recognition unit 13 comprises a data type identification module 14 which identifies the type of input data by comparing the input data with information stored in a prototype database 15. The prototype database 15 comprises samples of typed and handwritten characters (e.g., strokes, phonetical fonts, time-dependent representations, etc.) of one or more languages. It is to be understood that, depending on the application (e.g., language), the data type identification module 14 can employ any suitable technique known to those skilled in the art for identifying the type of input data.

20 For instance, in one embodiment, the data type identification module 14 may identify data types by examining the geometric patterns of the input data and comparing the geometric patterns with known patterns that characterize particular data types. For example, typed

5 textual data is characterized by features such as high level
symmetry of lines, different characters have parallel
strokes, sharp angles, and are relatively the same height,
etc. On the other hand, handwritten characters are
characterize by variations in size and direction of strokes,
etc. In addition, the prototype database 15 preferably
comprises different types of fonts for typed textual
characters, wherein the identification module 14 can compare
input textual data with the textual data in database 15 to
find a matching font (using scaling and a suitable distance
measure) to thereby define the data type and font of the
input data.

10 Furthermore, the manner in which the data is input can
be used by the identification module 14 to identify the data
type. Indeed, it is to be understood that textual data
15 (which is identified by the identification module 14) can be
input and stored in any preferred form depending on the
application. By way of example, there are various methods
by which Chinese characters may be input via a keyboard, as
20 well as systems that can recognize the type of input. For
instance, one method utilizes what is known as Pinyin,
which is a system for writing characters phonetically with
the Roman alphabet. A second method recognizes Chinese
characters based on the order in which the strokes of each

character are written. Another method for inputting and recognizing Chinese character is hybrid method that allows a first character to be entered phonetically and the next character to be entered via strokes. Therefore, the data type identification module 14 may utilize knowledge of such input methods to identify the data type.

An activation module 16 activates an appropriate recognition system based on the type of data identified by the identification module 14. For instance, if the identification module 14 determines that given textual data is handwriting data, then the data is sent to an AHR (automatic handwriting recognition) system 17 for processing. On the other hand, if the identification module 14 determines that given textual data is typed text data, then the data is sent to an OCR (optical character recognition) system 18 for processing.

Furthermore, to address textual data that is represented in different fonts and styles which depend on the time intervals of when the data was produced, the system can be adapted to recognize fonts of a textual input and then decode the textual input using a recognition module that is adapted to decode the given font. Indeed, it is to be appreciated that the recognition systems 17 and 18 are adapted to transcribe/recognize a textual input into a

string of semantic units using one or more vocabularies and language models that are based on semantic units. In particular, depending on the given language of the recorded text/handwriting data, the OCR system 18 and AHR system 17 may each operate in one of several modes, e.g., a syllable-based recognition mode or a morpheme-based recognition mode. In a syllable-based recognition mode, the AHR system 17 or OCR system 18 utilizes a vocabulary comprising syllables and syllable language model to transcribe the input text/handwriting data into a string(s) of syllables. Likewise, in a morpheme-based recognition mode, the AHR system 17 or OCR system 18 utilize a vocabulary comprising morphemes and a morpheme language model to transcribe the input text/handwriting data into a string(s) of morphemes. Preferred systems/methods for generating a language model based on semantic units (e.g., morphemes or syllables), which may be implemented with the recognition systems 17, 18, will be described in detail below with reference to Fig. 2.

It is to be understood that the AHR system 17 and the OCR system 18 may comprise any suitable conventional device or technique known to those skilled in the art, which is adapted appropriately to transcribe/recognize textual input into semantic units. For instance, the AHR system 17 may

employ the techniques described in United States Patent No. 5,577,135 to Grajski et al, issued on November 19, 1996 entitled "Handwriting Signal Processing Front-End For Handwriting Recognizers," which is incorporated herein by reference. In addition, the OCR system 18 may employ the techniques described in United States Patent No. 5,805,747 to Bradford, issued on September 8, 1998, entitled "Apparatus and Method For OCR Character and Confidence Determination Using Multiple OCR Devices," which is incorporated herein by reference. It is to be understood that although the preferred method for transcribing the textual data is performed automatically as described above, the step of transcribing may be performed manually using semantic-unit based stenography.

The semantic units that are output from the recognition systems 17, 18 are stored in semantic unit database 19 together with indexes (generated by an index generator module 20) that point to corresponding textual data that is stored in the textual data archive 12. In other words, depending on the application, decoded syllable and/or morpheme data, for example, is stored in database 19 together with indexes to the corresponding textual data in the textual data archive 12. The index generated by module 20 for a given textual input is specific to a particular

identified data type. Preferably, the indexing process utilizes time-stamping of the syllable and morphemes in the decoded strings so as to facilitate indexing, as is understood by those skilled in the art. This time stamping may be used to align the textual input with a corresponding audio data stream, wherein the textual input data (via semantic units) can be indexed to the corresponding audio frames using conventional techniques known to those skilled in the art.

It is to be appreciated that the index generated for a given data type may be converted (via an index converter module 21) to a universal index 23 using a conversion table 22 that comprises information of possible conversion of strokes, phoneme representations, characters, etc. The universal index 23 represents some general notations for different types of representation of textual data.

More specifically, the index generator module 20 will generate an index for each distinct data type (i.e., the same semantic units may have different indexes associated therewith which indicate the location where the same semantic units with a particular data type are stored). When a user enters a search query (comprising a given semantic unit) to perform a search using the indexes to locate words or word strings (in textual data archive 12)

that are associated with the given semantic unit, the query may also indicate the data type, in which case the index corresponding to the data type is used to locate corresponding words. Alternatively, the querying user may desire to find all possible words that contain the given semantic unit for all the different data types. The universal index 23 advantageously provides a mechanism to provide this search option since the universal index 23 points to all semantic units for all the different data types. For a given semantic unit, the corresponding universal index 23 points to a plurality of indexes, each corresponding to the given semantic unit for a different data type. Each index (which is generated by index generator module 20 for a given data type), in turn, points to the same semantic unit for the associated data type. Advantageously, a universal index 23 for a given semantic unit allows a person to search for all textual data in all the different data types that contain the given semantic unit.

The process of generating a universal index 23 for a given semantic unit is performed by the index converter module 21 and conversion table 22. The converter module 21 utilizes the table 22 to translate an index for a given data type to a universal index 23. The conversion table 22

comprises a map that specifies which data type indexes correspond to the universal index for the given semantic unit. For example, assume that **AAA** represents a given semantic unit for a textual (typed) data type and that **A'A'A'** represents the same semantic unit for handwritten data type. Assume further that **a1, a2, a3** are indexes to locations where typed textual data is stored that contains the semantic unit **AAA**, and that **a1', a2', a3'** are indexes to locations where handwritten data is stored that contains the semantic unit **A'A'A'**. The conversion table 22 may comprise an index **aa1, aa2, aa3** and a rule by which indexes **a1, a2, a3** and **a1', a2', a3'** can be obtained (e.g., **aa1**=100 and a rule that specifies to add 10000 to index **aa1** to obtain an index to a handwriting type and to add 20000 to **aa1** to obtain an index to textual type.) It is to be understood that the exemplary indexing system/method of Fig. 1 describes a scheme that involves object-indexing via semantic units (such as syllables, morphemes). It is to be appreciated that in other embodiments of the present invention, additional features can be implemented to index the textual data. For instance, the textual data can be indexed based on the author of the textual data. The labeling of textual-data with speaker names affords enhanced textual-search using

YOR9-2000-0144US1 (8728-375)

speaker names such as described in the Patent Application
U.S. Serial No. 09/294,214, filed on April 16, 1999,
entitled "*System and Method For Indexing and Querying Audio
Archive*," which is commonly assigned and incorporated herein
by reference. Indeed, by way of example, the user can
restrict a search of a given syllable query for an
individual or a list of individuals.

Furthermore, using a suitable biometric system known to
those skilled in the art, the stored textual data can
further indexed based on based on handwriting biometrics and
writing styles of persons associated with handwriting data.
Moreover, the stored textual-data can be also indexed based
on information such as the time and place where the textual
data was produced, etc.

The textual-data can also be indexed based on
pictorial-data that is placed on the same page of textual
data. As explained below, the pictorial data allows a user
to include with, e.g., a syllable query, other queries that
implement an image recognition/searching technique known to
those skilled in the art to find desired textual data that
is associated with a certain picture or pictures.

Furthermore, the index generator module may implement
the hierarchical index storage and searching techniques as
described in U.S. Patent Application Serial No. 09/108,544,

filed on July 1, 1998, entitled "Audio/Video Archive System and Method For Automatic Indexing and Searching", which is commonly assigned and incorporated herein by reference.

With this hierarchical indexing technique, the syllables/morphemes are included in one of a plurality of layers in a hierarchical pyramid. During a search process, each subset of records that is selected/modified based on the index information of a given layer is successively refined for each layer that is searched thereafter so as to narrow the search results in a hierarchical manner.

Referring now to Fig. 2, a block diagram illustrates a system/method for producing a language model based on semantic units. As explained above with reference to Fig. 1, one or more semantic unit-based language models are implemented with the recognition systems 17, 18 to decode textual data into strings of semantic units. A textual corpora in database 30 is transformed into a string of semantic units by a character-to-semantic unit mapper 31 (via mapping tables 32 that map strings of characters into, e.g., syllables). A counter 33 keeps track of the count for each of the different semantic units output from the character-to-semantic unit mapper 31.

To generate a language model of phonetic syllables, for example, it is important to know how syllables are

pronounced (since a person will write phonetic syllables for a word based on how the person pronounces the word).

Because the same syllable can have a different pronunciation, this data cannot be extracted directly from the textual corpus 30. Preferably, to obtain such information, pronunciation data stored in database 34 is utilized by the counter 33 to generate the appropriate count data. The pronunciation data 34 comprises data such as all possible pronunciations of words in the given language and/or how people transcribe them phonetically, which allows the counter 33 to differentiate between different pronunciations of the same written syllable.

More specifically, in the preferred embodiment illustrated in Fig. 2, the pronunciation data 34 is collected by transcribing audio data 35 and determining the different pronunciations for words. The audio data 35 may be transcribed manually 36 to generate a collection of transcriptions 38, or automatically using an automatic speech recognizer 37, which aligns phonetic syllables to a string of spoken syllables, to generate a collection of pronunciations 39. These collections are stored and indexed appropriately in the pronunciation database 34.

The counter 33 outputs the semantic units and corresponding counts 40 and phonetic syllable 41. The

semantic units 40 represent a character string that bears some semantic meaning (e.g., syllables or morphemes such as roots in Russian words which are not actual words, but represent a common semantic meaning for different words that contain the root). The phonetic syllables 41 comprise a special string of character that represent how some strings of characters (corresponding to the given semantic units), e.g., syllables, sound. The phonetic syllables 41 and semantic units 40 (e.g., syllables /morphemes) are used by a language model generator 42 to derive probabilities of distribution of phonetic syllables given syllable 41 and generate a language model based on semantic units. In particular, using techniques known in the art, the syllable counts and conditional distributions of phonetic syllables 41 are used to construct LM of phonetic syllables. For example, this procedure is similar to constructing a language model for classes such as described in the articles by Eugene Charniak, entitled "Statistical Language Learning", The MIT Press, Cambridge, 1996; and Frederick Jelinek, "Statistical Methods for Speech Recognition", The MIT Press, Cambridge, 1998.) Methods for generating a language model for morphemes, for example, are described in U.S. Patent No. 6,073,091, which issued on June 6, 2000 to Kanevsky et al., entitled "Apparatus and Method For Forming

5 A Filtered Inflected Language Model for Automatic Speech
Recognition" and U.S. Patent No. 5,835,888, which issued on
November 10, 1998 to Kanevsky, et al., entitled "Statistical
Language Model For Inflected Languages," both of which are
fully incorporated herein by reference.

Semantic Unit-Based Searching

Referring now to Fig. 3, a diagram illustrates a system
for searching a textual archive that is indexed based on
semantic units according to an embodiment of the present
invention. It is to be understood that Fig. 3 also
represents a high level flow diagram of a searching method
according to one aspect of the present invention. The
system 50 comprises an input/recording device 51 for
entering an input query (e.g., words and or semantic units).
It is to be understood that the input device may be, for
example, a keyboard for inputting a typed query, and OCR
system for recognizing/transcribing a typed query, an ASR
system for recognizing/transcribing a spoken query or an AHR
system for recognizing/transcribing a handwritten query.

20 The input query is processed by a query processor 52
(the details of which are described below with reference to
Fig. 4). The query processor 52 generates search attributes
that are processed by a semantic unit search engine 53

(e.g., the search engine 53 may interpret the query as a sequence of syllables/morphemes). The user query may comprise additional information that is used to localize the search. Based on the query attributes, the semantic unit search engine 53 identifies and retrieves relevant textual data stored in database 12 via the indexing and semantic unit information stored in the semantic unit database 19.

The query processor 52 outputs the search results that are received from the search engine 53 via an output device 54. The output device may be, for example, a computer monitor for displaying the search results or any conventional text-to-speech synthesis system to convert the search results to audio segments for audio playback to the user.

Referring now to Fig. 4, a diagram illustrates a system/method for processing a query according to an embodiment of the present invention. More specifically, the diagram of Fig. 4 illustrates a preferred operation of the query processor 52 of Fig. 3. The type of search media 60 comprising a user query may comprise handwriting data, typed text and/or pictorial data. A splitter module 61 processes the search media 60 and splits the search media into textual units 62 (that were utilized during the indexing process (Fig. 1) to index the textual archive 12). For example, the

5 textual units 62 output from the splitter module 61 may
comprise text portions (e.g., phrases, paragraphs, chapters,
poems, stories, etc.), words, syllables, phonetic syllables,
morphemes, characters, or semantic units (e.g., roots in
Slavic language). Furthermore, pictorial data can be split
into pictorial portions using, for example, the techniques
described in U.S. Patent application Serial No. 09/063,805,
filed on April 21, 1998, (IBM Docket No. YO998-141),
entitled "*Random Visual Patterns Used To Obtain Secured*
10 *Access*," which is commonly assigned and incorporated herein
by reference.

The user query may comprise words rather than a set of
syllables. In this case, a word search is performed by
converting the words into string of syllables using tables
(as described herein). For example, with a Slavic language,
15 a table may store words that are split in morphemes and
endings. The user query may comprise a relatively long
textual corpora rather than several words or syllables. The
user can produce a written text (for example, if he/she
manually types text into the computer). In these instances,
20 a textual corpora or typed words are mapped into a string of
syllables and a specific search mechanism can be used to
find textual data in the archive 12 that matches a long
string of syllables. For instance, the techniques disclosed

in the above-incorporated U.S. Patent No. 5,649,060 may be employed to match textual data with a reference textual corpora, even when a relatively low quality AHR is used. This technique exploits time stamping of a textual corpus and matches a small number of portions in the reference script with portions in the stored decoded output.

The textual units 62 are input to a query generator which generates search attributes based on the query. The query processor 63 may utilize a search assistance module 64 to provide other search attributes. For example, the search assistance module 64 may provide the hierarchical indexing information, e.g., syllables point to syllables, syllables point to words and words can point to phrases, using techniques as described in the above-incorporated U.S. Patent application Serial No. 09/108,544. In addition, the search assistance module 64 may comprises one or more systems such as a labeler that provides labels which are used to restrict a search (e.g., location, writer names, time period etc.), a time-stamping systems that uses time-stamping to index audio data and align it to textual data, and/or language model that is trained from a string of semantic units (e.g.. syllables) and increases the accuracy of mapping audio data into string of units (e.g. syllables). Indeed, as explained above, the textual data in archive 12

may be indexed via a syllable index and other additional information about writers who produced the handwriting data. The labeling of handwriting data with writer identification enhances the textual search using personal names. The stored textual data can be also associated with handwriting biometrics that provide additional information about speakers (for example, a conventional method known in the art is used to relate handwriting manner to a social user status, age, sex, etc.). Stored textual data can be also marked with labels providing information such as the time and/or location when/where the textual data was produced, etc.

Furthermore, the search assistance module 64 may be used to select the appropriate index for searching the archive. Indeed, as explained above, some of textual data (with indexes) can be stored in some preferred input method (for example, Pinyin method). If a user enters a query input using a different method (e.g., a hybrid method allows the first character to be entered phonetically and the following one by strokes), the search assistance module 64 can recognize the method with which the user input key words. Subsequently, during the search process when the textual archive 12 is searched, the search assistance module 64 will verify the input method by which the original

textual data was recorded (using, for example, the techniques described herein in connection with the data type identification module 14 (Fig. 1)). If the search assistance module 64 determines that the data is represented with a different input method, user input query is transformed into a query that corresponds with the index to such textual data. Similarly, if the system determines that the data being searched was recorded at times when different spelling was used, then the user input record will be transformed to match the appropriate index. It is to be appreciated that to convert the query to the appropriate format, the index converter module 21 discussed above (Fig.1) is preferably utilized to convert the index from the given data type to a universal index 23, which, as described above, allows a search to be performed for all data type indexes. In addition, the conversion table 22 (Fig. 1) to convert indexed from one data type format to another.

The search system further comprises an automatic word boundary marking system 65 that is utilized by the query generator 63 to determine which portion of the character segment that contains a given semantic unit, for example, should be displayed to the user. For example, the user will receive all "words" that contain a given semantic unit in some query. The words are defined automatically by module

65. The implementation of the word boundary marking system
65 is particularly useful for, e.g., written Chinese which
has no word boundaries. It is to be appreciated that any
suitable technique known by those skilled in the art may be
employed in module 65. For instance, techniques for
defining word boundaries that are based on statistical
characteristics are described in the article by C.J. Chen,
et al. "Continuous Speaker-Independent Putonhua Dictation
System," pp. 821-823, ICSP'96, 1996 3rd International
Conference on Signal Processing Proceedings, which is
incorporated herein by reference.

It is to be understood that the search results of a
given user query may be represented to the user in one of
various manners. For example, in one embodiment, the user
can first view the decoded (syllable) output (in some
printed or displayed format) and, after viewing the entire
decoded output, the user can select a desired portion of the
data to be represented to the user as it is stored in the
database (e.g., by clicking the mouse on the desired portion
of the textual output). In yet another embodiment, the
user can view pictorial data that is associated with textual
data that is returned in accordance with the user query. In
a further embodiment, the textual data can be displayed
starting from the syllable that was indicated by the user

query forward/back until either the user stops the displaying, or the user inputs the desired length (in the query) of the textual segment to be displayed. The initial displaying of the textual output in a decoded format makes sense since it may require less storage being represented in an efficient standard form such as ASCII). On the other hand, the process of displaying original written data may be slower since it requires displaying a data as it was scanned from manuscripts into computers. Furthermore, if there are pictures in a manuscript, the amount of stored image and handwritten data can be large in comparison with the decoded formatted output.

In summary, the use of semantic units for purposes of indexing and searching textual archives advantageously remedies the disadvantages associated with word-based textual database management. For example, the use of semantic units for managing textual databases provides font independence from languages whose fonts change with time. Moreover, the use of semantic units enhances recognition accuracy for, e.g., AHR and OCR systems that employ vocabularies and language models based on semantic units, especially for languages that comprise a significant amount of different word forms but have a finite amount of semantic units associated therewith.

Although illustrative embodiments have been described herein with reference to the accompanying drawings, it is to be understood that the present system and method is not limited to those precise embodiments, and that various other changes and modifications may be affected therein by one skilled in the art without departing from the scope or spirit of the invention. All such changes and modifications are intended to be included within the scope of the invention as defined by the appended claims.

WHAT IS CLAIMED IS:

1. A method for managing a textual database, comprising the steps of:

transcribing textual data into corresponding semantic units;

storing the textual data in the textual database; and
generating an index based on semantic units for indexing the stored textual data with the corresponding semantic units.

2. The method of claim 1, wherein the semantic units comprise syllables.

3. The method of claim 1, wherein the semantic units comprise morphemes.

4. The method of claim 1, wherein the textual data is associated with audio data, and wherein the step of indexing further comprises indexing the audio data with the semantic units.

5. The method of claim 1, wherein the step of transcribing comprises the step of time-stamping the semantic units.

YOR9-2000-0144US1 (8728-375)

6. The method of claim 1, wherein the step of transcribing comprises decoding the textual data with a recognition system utilizing a language model based on the semantic units.

5 7. The method of claim 1, wherein the step of transcribing is performed using semantic-unit based stenography.

10 8. The method of claim 1, wherein the step of generating an index comprises generating a hierarchical index wherein a semantic unit index points to another mode of data.

15 9. The method of claim 1, further comprising the steps of identifying the type of textual data, wherein the step of transcribing is performed based on the type of textual data identified.

10. The method of claim 1, further comprising the step of converting the index into a universal index which cross-references characters of different fonts.

11. The method of claim 1, further comprising the step of searching the textual database for target textual data using the semantic unit index.

12. The method of claim 11, further comprising the step of converting a target word into a string of semantic units to perform the searching step.

13. The method of claim 12, wherein the step of converting a target word is performed automatically using a character-to-semantic unit mapping table.

14. The method of claim 11, further comprising the step of displaying search results, wherein the target textual data is displayed starting from a corresponding semantic unit in a user query and commencing one of forward and backward for a given length based on a user request.

15. A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform method steps for managing a textual database, the method comprising the steps of:

transcribing textual data into corresponding semantic units;

storing the textual data in the textual database; and
generating an index based on semantic units for
indexing the stored textual data with the corresponding
semantic units.

5 16. A system for managing a textual database,
comprising:

a recognition system for transcribing textual data into
corresponding semantic units;

a textual database for storing the textual data; and

10 an index generator adapted to generate an index based
on semantic units, wherein the textual data stored in the
textual database is indexed with the corresponding semantic
units.

15 17. The system of claim 16, wherein the recognition
system comprises an OCR (optical character recognition)
system and an AHR (automatic handwriting recognition system)
for transcribing typed text and handwritten text,
respectively.

20 18. The system of claim 16, wherein the recognition
system comprises a language model based on semantic units.

19. The system of claim 16, further comprising an index converter adapted to convert the index into a universal index which cross-references characters of different fonts for a given language.

5 20. The system of claim 16, further comprising:

a query processor adapted to transform a search query for target textual data into corresponding semantic units; and

10 a search engine for searching the textual database based on the semantic units corresponding to the search query.

21. The system of claim 20, further comprising an automatic word boundary marking system that is applied to a search query.

**SYSTEM AND METHOD FOR MANAGING
A TEXTUAL ARCHIVE USING SEMANTIC UNITS**

ABSTRACT OF THE DISCLOSURE

A system and method for indexing and searching textual
archives using semantic units such as syllables and
morphemes. In one aspect, a system for indexing a textual
archive comprises an AHR (automatic handwriting recognition)
system and/or OCR (optical character recognition) system for
transcribing (decoding) textual input data (handwritten or
typed text) into a string of semantic units (e.g., syllables
or morphemes) using a statistical language model and
vocabulary based on semantic units (such as syllables or
morphemes). The string of semantic units that result from a
decoding process are stored in a semantic unit database and
indexed with pointers to the corresponding textual data in
the textual archive. In another aspect, a system for
searching a textual archive is provided, wherein a word (or
words) to be searched is rendered into a string of semantic
units (e.g., syllables or morphemes) depending on the
application. A search engine then compares the string of
semantic units (resulting from the input query) against the
decoded semantic unit database, and then identifies textual
data stored in the textual archive using the indexes that
were generated during a semantic unit-based indexing
process.

YOR9-2000-0144US1 (8728-375)




FIG. 1




FIG. 2




FIG. 3




FIG. 4

AS A BELOW NAMED INVENTOR, I hereby declare that:

My residence, post office address and citizenship are as stated next to my name.

I believe that I am the original, first and sole (*if only one name is listed below*), or an original, first and joint inventor (*if plural names are listed below*), of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**TITLE: SYSTEM AND METHOD FOR MANAGING A TEXTUAL ARCHIVE
USING SEMANTIC UNITS**

the specification of which either is attached hereto or indicates an attorney docket no. YOR9-2000-0144US1 (8728-375), or:

☐ was filed in the U.S. Patent & Trademark Office on _____ and assigned Serial No. _____,

☐ and (*if applicable*) was amended on _____,

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is material to patentability and to the examination of this application in accordance with Title 37 of the Code of Federal Regulations §1.56. I hereby claim foreign priority benefits under Title 35, U.S. Code §119(a)-(d) or §365(b) of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT international application which designated at least one country other than the United States, listed below and have also identified below any foreign applications for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Priority Claimed:

Yes [] No []

(Application Number) (Country) (Day/Month/Year filed)

Yes [] No []

(Application Number) (Country) (Day/Month/Year filed)

I hereby claim the benefit under Title 35, U.S. Code, §120 of any United States application(s), or §119(e) of any United States provisional application(s), or §365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application(s) in the manner provided by the first paragraph of Title 35, U.S. Code, §112, I acknowledge the duty to disclose information material to patentability as defined in Title 37, The Code of Federal Regulations, §1.56(a) which became available between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial Number) (Filing Date) (STATUS: patented, pending, abandoned)

(Application Serial Number) (Filing Date) (STATUS: patented, pending, abandoned)

I hereby appoint the following attorneys: MANNY W. SCHECTER, Reg. No. 31,722; LAUREN C. BRUZZONE, Reg. 35,082; TERRY J. ILARDI, Reg. 29,936; CHRISTOPHER A. HUGHES, Reg. No. 26,914; EDWARD A. PENNINGTON, Reg. No. 32,588; JOHN E. HOEL, Reg. No. 26,279; JOSEPH C. REDMOND, Jr., Reg. No. 18,753; WAYNE L. ELLENBOGEN, Reg. No. 43,602; STEPHEN C. KAUFMAN, Reg. No. 29,551; JAY P. SBROLLINI, Reg. No. 36,266; DAVID M. SHOFI, Reg. No. 39,835; ROBERT M. TREPP, Reg. No. 25,933; LOUIS P. HERZBERG, Reg. No. 41,500; DANIEL P. MORRIS, Reg. No. 32,053; DOUGLAS W. CAMERON, Reg. No. 31,596; LOUIS J. PERCELLO, Reg. No. 33,206; and PAUL J. OTTERSTEDT, Reg. No. 37,411; and MARIAN UNDERWEISER, Reg. No. 46,134; each of them of INTERNATIONAL BUSINESS MACHINES CORPORATION, Thomas J. Watson Research Center, P.O. Box 218, Yorktown Heights, New York 10598; to prosecute this application and to transact all business in the U.S. Patent and Trademark Office connected therewith and with any divisional, continuation, continuation-in-part, reissue or re-examination application, with full power of appointment and with full power to substitute an associate attorney or agent, and to receive all patents which may issue thereon, and request that all correspondence be addressed to:

Frank Chau, Esq.
F. CHAU & ASSOCIATES, LLP
1900 Hempstead Turnpike, Suite 501
East Meadow, New York 11554
Tel.: 516-357-0091

I HEREBY DECLARE that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under §1001 of Title 18 U.S. Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

FULL NAME OF FIRST OR SOLE INVENTOR: Julian C. Chen Citizenship U.S.A.

Inventor's signature:  Date: 9/11/00

Residence: White Plains NY 10603

Post Office Address: 29 Hawthorne Street, White Plains, NY 10603


FULL NAME OF SECOND JOINT INVENTOR: Dimitri Kanevsky Citizenship U.S.A.

Inventor's signature:  Date: 9/11/00

Residence: Ossining, NY 10562

Post Office Address: 1358 Spring Valley Road, Ossining, NY 10562

FULL NAME OF THIRD JOINT INVENTOR: Wlodek W. Zadrozny Citizenship U.S.A.

Inventor's signature:  Date: 9/12/00

Residence: Tarrytown, NY 10591

Post Office Address: 145 Neperan Rd., Tarrytown, NY 10591

FULL NAME OF FOURTH JOINT INVENTOR: _____ Citizenship _____

Inventor's signature: _____ Date: _____

Residence: _____

Post Office Address: _____

FULL NAME OF FIFTH JOINT INVENTOR: _____ Citizenship _____

Inventor's signature: _____ Date: _____

Residence: _____

Post Office Address: _____

FULL NAME OF SIXTH JOINT INVENTOR: _____ Citizenship _____

Inventor's signature: _____ Date: _____

Residence: _____

Post Office Address: _____